

Main features

HTFU XRV-K Cassette 60x60 round flow



Infrared remote control



- 5 power levels: 1.50~4.50 kW.
- TFP 352 IHRS panel with 360° air diffusion.
- Wide louvre oscillation range up to 40°.
- Electrical box inside the unit body.
- Pre-set for the connection of a channel for the intake of external air.
- Condensate drain pump with possibility of raising the discharge up to 360 mm from the outlet height.

Model	HTFU 155 XRV-K*		HTFU 225 XRV-K		HTFU 285 XRV-K		HTFU 365 XRV-K		HTFU 455 XRV-K		
Rated cooling capacity	kW	1.5	2.2		2.8		3.6		4.5		
Rated heating capacity	kW	1.7	2.4		3.2		4		5		
Electrical data											
Power supply	Ph-V-Hz	1-220~240V-50Hz									
Electrical absorption	W	14	15		16		21				
Product specifications											
Air flow	L/M/H	m³/h	364 / 449 / 526			405 / 503 / 576			409 / 521 / 610		
Sound pressure level at 1.4 m	L/M/H	dB(A)	21/32/33			22/32/34			27/34/40		
Sound power level	L/M/H	dB(A)	34/44/45			35/44/46			41/47/52		
Dimensions	LxHxD	mm	570x260x570								
	Net weight	Kg	16						17.5		
Refrigerant connections	Liquid/Gas	Ø mm (inch)				6.35 (1/4") - 12.7 (1/2")					
Condensate drain		Ø mm	25								
Serial control		type	IR Remote control								
Accessories											
Decorative panel			TFP 352 IHR-S								
Panel dimensions	LxHxD	mm	647x50x647								
	Net weight	Kg	2.5								
Optional parts											
Wired remote control			DTW 3 IHXR TOUCH / DTW IHXR SIMPLY / DTWS 4 IHXR COMPACT								
Centralised control			See compatibility table on p. 69								

* Can only be connected to XRV PLUS MINI Inverter line outdoor units up to 18 kW.

Main features

HTBU XRV-K Cassette 84x84



Infrared remote control



- 5 power levels: 5.60~14.00 kW.
- Opening louvre angle up to 42°.
- Low resistance and low noise fan profile
- TBP 712 IHXR panel and 4 removable corners for easy installation.
- Condensate drain pump with possibility of raising the discharge up to 360 mm from the outlet height.
- Internal electronic control (accessible from the panel).
- Pre-set for connecting a duct for outside air intake and a duct for cooling/heating a small adjacent room.

Model	HTBU 565 XRV-K		HTBU 715 XRV-K		HTBU 905 XRV-K		HTBU 1125 XRV-K		HTBU 1405 XRV-K		
Rated cooling capacity	kW	5.6	7.1		9		11.2		14		
Rated heating capacity	kW	6.3	8		10		12.5		15		
Electrical data											
Power supply	Ph-V-Hz	1-220~240V-50Hz									
Electrical absorption	W	31	46		75		94				
Product specifications											
Air flow	L/M/H	m³/h	704/857/1029		748/996/1200		1030/1239/1596		1280/1500/1800		
Sound pressure level at 1.4 m	L/M/H	dB(A)	34/38/43		34/39/45		36/41/47		44/47/50		
Sound power level	L/M/H	dB(A)	47/50/54		47/51/56		49/53/58		48/57/61		
Dimensions	LxHxD	mm	840x230x840						840x300x840		
	Net weight	Kg	24						27		30
Refrigerant connections	Liquid/Gas	Ø mm (inch)				9.52 (3/8") - 15.9 (5/8")					
Condensate drain		Ø mm	32								
Serial control		type	IR Remote control								
Accessories											
Decorative panel			TBP 712 IHXR								
Panel dimensions	LxHxD	mm	950x70x950								
	Net weight	Kg	5.8								
Optional parts											
Wired remote control			DTW 3 IHXR TOUCH / DTW IHXR SIMPLY / DTWS 4 IHXR COMPACT								
Centralised control			See compatibility table on p. 69								